

PRODUCT FEATURES

DRAINMINOR C units have been designed to pump waste water from a combination oven, dish / glasswasher, commercial sink / basin or any situation where waste water needs to be collected and pumped to the drainage system. They have been specially constructed to handle hot water up to 60°C, or even higher temperatures for short periods, and can deal with up to 10mm solids. An important feature of the unit is its high head pumping capability enables it to handle difficult, awkward or long discharge pipe runs 5 metres vertically, 50 metres horizontally or a combination of both.



HIGH LEVEL ALARM - *Side Mounted Float*

These units are designed for connection to a 240 V supply circuit. The alarm buzzer has a minimum volume of 80 dBA (at 1m distance).

A rechargeable battery is fitted in case of mains electricity supply failure.

The float mechanism provided must be attached through the side of the tank and positioned in an area away from the inverts from sinks, dishwashers, glasswashers etc. to prevent ingress of water inadvertently actuating the horizontal float switch mechanism.



DRAIN DOSING SYSTEM - *Battery Operated*

Our automatic, Battery Operate, dosing pump is the essential partner for your waste water system.

It allows you to continuously and evenly dispense our biological dosing fluid (sold separately) into your unit over a 24/7 period meaning that it is always performing at its best!

It provides a reliable drain dosing solution for smaller catering Establishments.

