DATA SHEET

DrainMajor 1030 (3ph)

Wastewater Pumping System

PART NO.	DOC. REV.	ISSUE DATE	MANUFACTURER	SHEET
154	1	29.10.2026	PTL/Jung Pumpen GmbH	01 / 03

GENERAL DESCRIPTION

DrainMajor 1030 (3ph) features a heavy-duty tank and submersible pump for automatically pumping wastewater from commercial kitchens, tea points and similar applications.

TANK CONSTRUCTION

Manufactured from recyclable polyethylene and fully rigged with internal pipework and a non-return valve. The lid is secured with easy-to-remove hand screws and seats on a custom-moulded, fitted rubber seal.

TANK VOLUME	**74.8 litres**
USABLE VOLUME (APPROX.)	**49.8 litres**
MINIMUM INVERT HEIGHT	**185 mm**
DISCHARGE OUTLET	**1½" BSP male + NRV**
TANK VENTING	**1¼" min. to air or MicroVent**

Inlet connection

To suit site layout, bring all inverts into the side of the tank by drilling a hole and fitting an appropriate tank connector.

Made from recyclable polyethylene

Recycling polyethylene is cost-effective and successful — greener than incineration, more eco-friendly than landfill, and readily reprocessed into new products.

TANK DIMENSIONS




FIG. 1 — TANK PLAN & ELEVATION, DIMENSIONS IN MM

DATA SHEET

DrainMajor 1030 (3ph)

Pump — US 103 DS Submersible

PUMP FEATURES

- Safe to run dry
- 30 mm free passage
- Controllable oil chamber
- SiC mechanical seal independent of sense of rotation
- Replaceable moisture-sealed cable inlet
- Fluid temperature 35 °C continuous, 60 °C for 10 min.

DESCRIPTION

The heavy-duty centrifugal submersible drainage pump US 103 DS is suitable for wastewater and capable of handling soft solids up to 30 mm in particle size.

PUMP TYPE	**US 103 DS**
OVERALL HEIGHT	**410 mm**
OVERALL DIAMETER	**210-195 mm**
SWITCH DIFFERENTIAL	**135–185 mm**

PERFORMANCE CURVE — US 103 DS




FIG. 2 — US 103 DS HEAD (H) VS. FLOW (Q)

SWITCHING POINTS

LEVEL — ON	LEVEL — OFF
185 mm from base	**135 mm from base**

DATA SHEET

DrainMajor 1030 (3ph)

Technical Data & Scope of Supply


MECHANICAL DATA	
Pump	Vertical single stage
Free passage	30 mm
Bearing	Ball bearing, grease-lubricated
Seal — motor side	Duplex rotary shaft seals
Oil chamber	Yes
Seal — medium side	SiC mechanical seal
Thermal protection	Yes
Shaft	Stainless steel
Impeller	Vortex impeller, GFK
Motor housing	Stainless steel
Pump housing	Grey cast iron
Submersible	Yes
Pressure outlet	1½" female

ELECTRICAL DATA	
Voltage	3/PE — 400 V
Motor rating P1	1.36 kW
Motor rating P2	1.60 kW
Current	2.4 A
Type of enclosure	IP 68
Insulation class	B
Winding thermostat	Yes
Motor protection	Integrated
Plug	CEE

Type	Code No.	Power line	Wires	Weight
WITH BUILT-IN LEVEL CONTROL				
US 103 DS, 10 m cable	JP09259	10 m H07RN-F	4G1,0	15.0 kg

INSTALLATION NOTES

- This unit is for wastewater only.
- Ensure the location of the DrainMajor enables the lid to be easily removed for regular inspection and maintenance.
- If the discharge pipework connection to a soil stack, manhole etc. is below the discharge outlet of the tank, an anti-syphon unit must be fitted at the highest point of the discharge pipework.



2 YEAR WARRANTY

The DrainMajor 1030 (3ph) comes complete with a two-year warranty from Pump Technology Ltd.

Official Distributor and Stockist Authorised by Jung Pumpen GmbH.
Pump Technology Ltd. reserves the right to change the specification without prior notice.
Part No. 154, Data Sheet Rev. 1, 29.10.2026.