DATA SHEET

DrainMajor 60 (3ph)

Wastewater Pumping System

PART NO.	DOC. REV.	ISSUE DATE	MANUFACTURER	SHEET
132	1	28.10.2026	PTL/Jung Pumpen GmbH	01 / 03

GENERAL DESCRIPTION

DrainMajor 60 (3ph) features a heavy-duty tank and submersible pump for automatically pumping wastewater from commercial kitchens, tea points and similar applications.

TANK CONSTRUCTION

Manufactured from recyclable polyethylene and fully rigged with internal pipework and a non-return valve. The lid is secured with easy-to-remove hand screws and seats on a custom-moulded, fitted rubber seal.

TANK VOLUME	**74.8 litres**
USABLE VOLUME (APPROX.)	**49.8 litres**
MINIMUM INVERT HEIGHT	**130 mm**
DISCHARGE OUTLET	**1½" BSP male + NRV**
TANK VENTING	**1¼" min. to air or MicroVent**

Inlet connection

To suit site layout, bring all inverts into the side of the tank by drilling a hole and fitting an appropriate tank connector.

Made from recyclable polyethylene

Recycling polyethylene is cost-effective and successful — greener than incineration, more eco-friendly than landfill, and readily reprocessed into new products.

TANK DIMENSIONS




FIG. 1 — TANK PLAN & ELEVATION, DIMENSIONS IN MM

DrainMajor 60 (3ph)

Pump — U6K DS Submersible

PUMP FEATURES

- Safe to run dry
- 10 mm free passage with EIP technology
- Cooling jacket for motor housing
- SiC mechanical seal independent of sense of rotation
- Replaceable moisture-sealed cable inlet
- Flushing device
- Fluid temperature 35 °C continuous, 60 °C for 10 min.

DESCRIPTION

The heavy-duty centrifugal submersible drainage pump U6K DS is suitable for wastewater and capable of handling soft solids up to 10 mm in particle size.

PUMP TYPE	**U6K DS**
OVERALL HEIGHT	**335 mm**
OVERALL DIAMETER	**Ø175 mm**
SWITCH DIFFERENTIAL	**80–130 mm**

PERFORMANCE CURVE — U6K DS




FIG. 2 — U6K DS HEAD (H) VS. FLOW (Q)

SWITCHING POINTS

LEVEL — ON	LEVEL — OFF
130 mm from base	**80 mm from base**

DATA SHEET

DrainMajor 60 (3ph)

Technical Data & Scope of Supply


MECHANICAL DATA	
Pump	Vertical single stage
Free passage	10 mm
Bearing	Ball bearing, grease-lubricated
Seal — motor side	Rotary shaft seal
Oil chamber	Yes
Seal — medium side	SiC mechanical seal
Thermal protection	Yes
Shaft	Stainless steel
Impeller	Vortex impeller, GFK
Motor housing	Stainless steel
Pump housing	GRP
Submersible	Yes
Pressure outlet	1¼"

ELECTRICAL DATA	
Voltage	3/PE — 400 V
Motor rating P1	0.75 kW
Motor rating P2	0.55 kW
Current	1.3 A
Type of enclosure	IP 68
Insulation class	B
Winding thermostat	Yes
Motor protection	Integrated
Plug	CEE

Type	Code No.	Power line	Wires	Weight
WITH BUILT-IN LEVEL CONTROL				
U6K DS, 4 m cable	JP00229	4 m H07RN-F	4G1,0	5.9 kg

INSTALLATION NOTES

- This unit is for wastewater only.
- Ensure the location of the DrainMajor enables the lid to be easily removed for regular inspection and maintenance.
- If the discharge pipework connection to a soil stack, manhole etc. is below the discharge outlet of the tank, an anti-syphon unit must be fitted at the highest point of the discharge pipework.



2 YEAR WARRANTY

The DrainMajor 60 (3ph) comes complete with a two-year warranty from Pump Technology Ltd.

Official Distributor and Stockist Authorised by Jung Pumpen GmbH.
Pump Technology Ltd. reserves the right to change the specification without prior notice.
Part No. 132, Data Sheet Rev. 1, 28.10.2026.